






DYNEX cavityclosers

Features & Benefits

A new range of uPVC cavity closers designed for use on drained cavities behind the exterior cladding and meet the requirements of NZBC Acceptable Solution E2/AS1 paragraph 9.1.8.3. Made in New Zealand using high quality UV stabilised & 100% recyclable uPVC material. All closers have innovative batten locator. BRANZ Appraised.

	20mm Cavity Closer	
	Standard 20mm Cavity Closer with an added feature of a soft seal outer lip.	Closes unsightly gaps created by variation in cavity thickness or cladding imperfections.
	30mm Cavity Closer	
	A thicker and stronger Cavity Closer with built-in Cant Strip, designed for Timber Weatherboard applications.	Won't crush when bottom Weatherboard is fixed.
	35mm Cavity Closer	
	A thicker and stronger Cavity Closer with built-in Cant Strip, designed for Timber Weatherboard applications.	Won't crush when bottom Weatherboard is fixed.
	40-50mm Cavity Closer	
	2 in 1 sized cavity closer that can be easily modified from 50mm to 40mm applications.	Reduced inventory & multiple applications.
	Raked Roof Cavity Closer	
	A 20mm Cavity Closer complete with uniquely designed bulb seal.	Hides unsightly gaps on a raking roof created by board lapping, aiding vermin proofing and meeting building code requirements.