



## Standard Range

## **DYNEX** cavityclosers

A comprehensive range of uPVC Cavity Closers suitable for use on drained cavities behind the exterior cladding, that meet the requirements of NZBC Acceptable Solution E2/AS1 paragraph 9.1.8.3.

Designed and made in New Zealand using high quality UV stabilised and 100% recyclable uPVC material. Proudly BRANZ Appraised.

## Standard Range

Our standard Cavity Closers are designed with unique innovative features to cover a variety of building applications.

## Key features:

- Flexible tip to hide discrepancies in claddings (20mm, 45mm and raked roof closers)
- Supplied in 3 metre lengths
- Recyclable materials
- BRANZ appraised
- Designed and made in NZ

SIZE	DESCRIPTION	PART NO.	BARCODE
20mm	An innovative Soft Tip cavity closer with a flexible lip designed to close the gap at the bottom of drained cavitites. For use on different types of buildings and claddings. Available in 20mm and 45mm. Supplied in 3m lengths (White)	CAVT020WHT3	9 421029 070118 >
45mm		CAVT045WHT3	9 421029 070200 >
Raked roof	Similar to the Soft Tip closer. It features a bulb seal and is ideal for raked rooflines behind weatherboard claddings to fill gaps that typically occur. Available in 20mm. Supplied in 3m lengths (White)	CAVT025WHT3	9 421029 070125 >
30mm	A thicker stronger Cavity Closer with built-in Cant Strip designed for timber weatherboard applications, that won't crush when the bottom weatherboard is fixed. Available in 30mm and 35mm. Supplied in 3m lengths (White)	CAVT030WHT3	9 421029 070132 >
35mm		CAVT035WHT3	9 421029"070149" >
40/50mm	2 in 1 sized cavity closer that can be easily modified from 50mm to 40mm applications by snapping off the front face. Available in 40/50mm. Supplied in 3m lengths (White)	CAVT040WHT3	9 421029 070156 >



Contact Dynex for more information or to request a sample. PHONE 0800 439 639 FAX 0800 737 375

dynex.nz